

HT 248 PPB

60,45 cm / 23.8" Diagonal
LED Backlight – Format 16:9

- 23.8" Touch Monitor LED Backlight
- 1920 x 1080 Full HD Display
- P-Cap 10-Point Touch
- 178° / 178° Ultra Wide Viewing Angle
- Hardness $\geq 7H$
- Display Port + HDMI + VGA Inputs
- HUB USB 3.0: 1 up, 2 down
- Edge-to-Edge Glass
- Ultra-Slim Design
- Built-In Stereo Speakers
- Ergonomic Smart adjustable stand
- Flicker Free and Low Blue Light Mode
- VESA Mount + Including Landscape and Portrait mounting options



60,45 cm / 23.8"

Part. No.: HT 248 PPB

SIZE, RESOLUTION



23.8"
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, SPEAKER



HDMI
Display Port
VGA



Built-In
Stereo Speaker

VIEWING ANGLE, VESA



178° Ultra-Wide
Viewing Angle



VESA
Wall-Mountable

TOUCH DISPLAY FEATURES



10 Point
Touch



USB
Link





$\geq 7H$
Surface



Adj
Stand

Display Size	60,45cm / 23.8" Diagonal
Panel Type	TFT – LED Backlight
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	300 cd/m ² (Panel) – 250 cd/m ² (Monitor)
Contrast (Typ.)	3.000:1 (Typical)
Contrast (Active)	10.000.000:1 (Active)
Viewing Angle L/R; U/D	178° H – 178° V (CR > 10)
Response Time	8 msec
Pixel Pitch	0,2745 (H) x 0,2745 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch
Display Colors	16.7M Colors
Horizontal Frequency	31 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	D-Sub (VGA)
Input 2	HDMI 1.4
Input 3	Display Port 1.2
Buil-in Speakers	Yes, 1,5W x 2; Earphone Audio Out x 1
Power Consumption	On: 14W; Stand-by: 0,3W; Off: 0,3W
AC Power Range	External Power Adaptor: Input: AC 100 ~ 240 Volt; 50 ~ 60 Hz Output: 12V – 3A
Product Dimensions	549,84 x 49,15 x 333,2 mm (W x D x H)
Packing Dimensions	630 x 123 x 439 mm (W x D x H)
Net / Gross Weight	4,5 Kg / 6,1 Kg
Bezel & Color Plan	Bezel: Black texture; Back cover: Black texture; Arm: Metal black

VESA Mounting	100 x 100 mm
Monitor Stand	Smart Adjustable Stand ("book" type)
Tilt / Kensington Lock	15° ~ 70° (+1/-3°) / Yes
Display Protection	Thickness 1,2 ± 0,1 mm; Material OGS
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥88%
Controls	Menü, Bri (+), Vol (-), Input/Enter, Power
Color	Warm, Natural, Cool, User Mode
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	15 OSD Languages
Accessory	Power Supply; Power Cable (1,5m); HDMI Cable (1,5m); USB 3.0 (B-A) Cable (1,8m); Warranty Card; QSG
Other Features	USB 3.0 HUB: 1 Up stream, 2 Down stream Flicker Free and Low Blue Light Mode
Orientation	Landscape, Portrait



Supplier's Name	HANNSpree
Model Name	HT248PPB
Energy efficiency class for standard Dynamic Range (SDR)	D
Annual Energy Power Consumption (kWh/1000h)	14 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	14 W
Off mode power demand (W)	0,3 W
Standby mode power demand (W)	0,3 W
Screen Diagonal (cm / inches)	60,45 / 23.8"
Resolution	1920 x 1080

PART. NO.:
HT 248 PPB



